TECHNICAL DATA SHEET

HIGHJEN Drain Opener · Document HXC-TDS-HJ-DO · Version 2.1 · 11.11.2026

Product	HIGHJEN Drain Opener
Description	Works with water to break down residue, grease and dirt in drain pipes — for kitchens, bathrooms and other household drains.
Pack formats	350 g (7 uses)



Directions for use

Manufacturer information.

1. Pour approximately 50 g of the product into the affected drain, then immediately add 2 liters of boiling water. Allow to sit for 2–3 minutes, then flush with cold water. Repeat the process if necessary.
2. Do not use this product in conjunction with a plunger. Avoid mixing with acids or other household products. Do not pour the product into standing or cold water. Avoid use if the blockage is caused by paper, plastic, or metal objects. Overdosing may exacerbate the blockage, so use the recommended amount cautiously.

Typical properties

Parameter	Typical value	Specification
Appearance	White granules, matches standard	–
Odour	Odourless	–
Sodium hydroxide (NaOH) content, %	99.0	≥ 98.0
Sodium carbonate (Na_2CO_3), %	0.6	≤ 1.0
pH (1 % aqueous solution, 20 °C)	13.5	≥ 13.0

Specification approved by the HomeXCare chemist on 11.11.2026 (certificate-of-analysis parameters). Typical values are average values for information; each lot is released against the specification.

Safety, storage and documents

Hazard classification (CLP)	Danger (GHS05): H314 Causes severe skin burns and eye damage.
Packaging requirements	Child-resistant closure and tactile warning of danger (CLP Annex II, 3.1 and 3.2).
Transport	UN 1823, SODIUM HYDROXIDE, SOLID, class 8, packing group II (ADR/RID, IMDG, IATA).
Shelf life	3–5 years from the date of production in the unopened original packaging, stored as recommended.
Storage	Keep tightly closed in the original packaging in a dry place, away from acids and out of the reach of children; the product absorbs moisture from the air.
Documents	Safety Data Sheet (English, REACH Annex II as amended by Regulation (EU) 2020/878); product page with documents and directions: www.homexcare.com/products/drain-opener/.

Packaging and logistics

Pack	Retail unit	Carton (mm)	Units / carton	Cartons / pallet	Units / pallet	Cartons / FTL	Units / FTL
350 g	7 uses	248×318×140	20	176	3,520	2,738	54,760

Pallet: Euro pallet 80 × 120 cm. FTL = full truck load (13.6 m trailer), limited to 23 t gross weight. Logistics data are indicative and are confirmed with each order (packing list); gross weights, barcodes (EAN) and pallet patterns on request.

This data sheet describes the product as supplied and is given in good faith; it does not replace the label or the Safety Data Sheet. Further technical data on request.

HomeXCare Kozmetik Sanayi ve Ticaret Ltd. Şti. (HOMEXCARE COSMETICS) · Tahtakale Mah. Fırat 1 Cad. Bahçe City B Blok No: 4/1 İç Kapı No: 50, Avcılar / İstanbul, Türkiye · +90 534 010 11 05 · info@homexcare.com · www.homexcare.com